



RJ Speed Legends (2 cell)

(Updated 10/13/2023)

Chassis

1. RJ Speed legends kit only.
2. Servo can be mounted in any location in the front of car.
3. No shaving any of the chassis or drilling holes to reduce weight.
4. Only RJ Speed legends chassis parts or similar TK Racing can be used.
5. Bearings are legal to use.
6. Turnbuckles are ok to be used for steering linkage only.
7. SPEC Gearing. Only an 81-tooth spur and either a 18-tooth pinion or lower. 48 pitch gears only.
8. Any pan car front spring.
9. Factory front bumper must remain on car.
10. Can substitute similar TK Racing parts.
11. All parts must be available for purchase from the RJ Speed website or TK Racing website/facebook page.
12. No printed parts. No side trays for weight.

Body

1. Only RJ Speed full fender legends bodies are legal.
2. No scraping of the body or drilling holes in the chassis to reduce weight.
3. Must use RJ Speed Legend body cut on the cut lines.
4. Windows must remain intact.
5. Body post/mount holes must be punched in the factory marked hole locations.

Tires

Blue, purple or yellow stripe spec tire or rubber CRC tires are the only legal tires

Electronics

1. Any steering servo can be used.
2. Any esc can be used in blinky mode.
3. Trinity Equalizer 21.5 motor. **MUST BE MOUNTED ON THE RIGHT SIDE.**
4. Any 1800 Mah 6cell Nihm battery pack or ROAR Legal 2 cell lipo battery max 5200 Mah